

Attorney Docket No. 249163US2SDIV
Inventor: Yusuke KAWAGUCHI et al
Preliminary Amendment filed: March 3, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A power MOSFET device comprising:
 - a low resistance substrate of the first conductivity type;
 - a high resistance epitaxial layer of the first conductivity type formed on the low resistance substrate;
 - a base layer of the second conductivity type formed in a surface region of said high resistance epitaxial layer;
 - a source region of the first conductivity type formed in a surface region of the base layer;
 - a gate insulating film formed on the surface of said base layer so as to contact said source region;
 - a gate electrode formed on said gate insulating film; and
 - an LDD layer of the first conductivity type formed on the surface of said high resistance epitaxial layer oppositely relative to said source region and said gate electrode;wherein said LDD layer and said low resistance substrate are connected to each other by said high resistance epitaxial layer.
2. (Original) The device according to claim 1, wherein
said LDD layer has a bottom section formed at a level shallower than said base layer.

Attorney Docket No. 249163US2SDIV
Inventor: Yusuke KAWAGUCHI et al
Preliminary Amendment filed: March 3, 2004

3. (Original) The device according to claim 1, wherein
said LDD layer has a bottom section formed at a level deeper than said base layer.
4. (Original) The device according to claim 1, further comprising:
a low resistance intermediate layer of the first conductivity type formed in a lateral
section of said base layer facing said LDD layer and a region of said epitaxial layer held in
contact with said LDD layer and having an impurity density higher than said epitaxial layer.
5. (Original) The device according to claim 1, further comprising:
a current conducting layer formed in said epitaxial layer to directly continue from said
LDD layer so as to project toward said low resistance substrate.
6. (Original) The device according to claim 1, wherein
the bottom of said base layer is held in contact with said low resistance substrate.
7. (Original) The device according to claim 1, wherein
said LDD layer is formed in a self-aligning manner by using said gate electrode as
mask.
8. (Original) The device according to claim 2, wherein
said LDD layer is formed in a self-aligning manner by using said gate electrode as
mask.
9. (Original) The device according to claim 3, wherein

said LDD layer is formed in a self-aligning manner by using said gate electrode as mask.

10. (Original) The device according to claim 4, wherein
said LDD layer is formed in a self-aligning manner by using said gate electrode as mask.

11. (Original) The device according to claim 5, wherein
said LDD layer is formed in a self-aligning manner by using said gate electrode as mask.

12. (Original) The device according to claim 6, wherein
said LDD layer is formed in a self-aligning manner by using said gate electrode as mask.

13. (Original) The device according to claim 1, further comprising:
an extension layer of the second conductivity type formed in a lateral section of said base layer facing said LDD layer and a surface region of said epitaxial layer and at least held in contact with said LDD layer, said extension layer having an impurity concentration lower than that of said base layer.

Attorney Docket No. 249163US2SDIV
Inventor: Yusuke KAWAGUCHI et al
Preliminary Amendment filed: March 3, 2004

14. (Original) The device according to claim 13, wherein
said extension layer of the second conductivity type is formed in said epitaxial layer
so as to cover the periphery of said base layer.

15. (Original) The device according to claim 13, wherein
said extension layer of the second conductivity type is formed in said epitaxial layer
between said base layer and said LDD layer.

16. (Original) The device according to claim 15, wherein
said extension layer of the second conductivity type is formed in said epitaxial layer
so as to cover the periphery of said base layer.

17. (Original) The device according to claim 13, wherein
the bottom of said base layer is held in contact with said low resistance substrate.

18. (Original) The device according to claim 14, wherein
the bottom of said base layer is held in contact with said low resistance substrate.

19. (Original) The device according to claim 15, wherein
the bottom of said base layer is held in contact with said low resistance substrate.

20. (Original) The device according to claim 17, wherein
said LDD layer is formed in a self-aligning manner by using said gate electrode as a
mask.

21. (Original) The device according to claim 1, wherein
said LDD layer has a length between about $0.7\ \mu\text{m}$ and about $0.8\ \mu\text{m}$.

22. (Original) The device according to claim 13, wherein
said LDD layer has a length between about $0.7\ \mu\text{m}$ and about $0.8\ \mu\text{m}$.

23. (Original) The device according to claim 21, wherein
the dose of said LDD layer is not higher than $6.0 \times 10^{11}/\text{cm}^2$.

24. (Original) The device according to claim 22, wherein
the dose of said LDD layer is not higher than $6.0 \times 10^{11}/\text{cm}^2$.

25. (Canceled)

26. (Canceled)

27. (Original) The device according to claim 25, wherein
said sinker layer has a trench formed so as to extend from said LDD layer to said low
resistance substrate, a low resistance layer of the first conductivity type formed on a lateral
surface of said trench and an insulating film buried in said trench.

28. (Original) The device according to claim 25, wherein
said sinker layer has a trench formed so as extend from said LDD layer to said low resistance substrate and a low resistance semiconductor layer of the first conductivity type buried in said trench.

29. (Original) The device according to claim 25, wherein
said sinker layer has a trench formed so as extend from said LDD layer to said low resistance substrate and a metal layer buried in said trench.

30. (Canceled)

31. (Canceled)

32. (Original) The device according to claim 27, wherein
said extension layer of the second conductivity type is formed so as to extend to said sinker layer and cover the periphery of said base layer.

33. (Original) The device according to claim 28, wherein
said extension layer of the second conductivity type is formed so as to extend to said sinker layer and cover the periphery of said base layer.

34. (Original) The device according to claim 29, wherein
said extension layer of the second conductivity type is formed so as to extend to said sinker layer and cover the periphery of said base layer.

Attorney Docket No. 249163US2SDIV
Inventor: Yusuke KAWAGUCHI et al
Preliminary Amendment filed: March 3, 2004

35. (Canceled)

36. (Canceled)

37. (Canceled)

38. (Canceled)

39. (Original) The device according to claim 27, wherein
the bottom of said base layer is held in contact with said low resistance substrate.

40. (Original) The device according to claim 28, wherein
the bottom of said base layer is held in contact with said low resistance substrate.

41. (Original) The device according to claim 29, wherein
the bottom of said base layer is held in contact with said low resistance substrate.

42. (Canceled)

43. (Canceled)

44. (Canceled)

45. (Canceled)

46. (Canceled)

47. (Canceled)